

# CS SERIES SEALER



## MACHINE FEATURES & SPECS

### CHANGEOVER TIME

2

MINUTES

### SPEED PER MINUTE

40

PACKAGES

### INTEGRATION ABILITY

FULL

WITH DELKOR  
EQUIPMENT

### PACKAGE TYPES

2

RSC, RSC TOP

### SEAL OPTIONS

2

GLUE, TAPE

### MACHINE HAND

RIGHT HAND  
LEFT HAND

### FRAME MATERIALS

PAINTED CARBON STEEL  
OR STAINLESS STEEL

### UTILITIES POWER

480 VAC  
50 - 60HZ  
30 AMPS

### UTILITIES AIR

5 SCFM @ 80 PSIG

### SYSTEM PLC

ALLEN-BRADLEY  
COMPACT LOGIX

### SYSTEM HMI

ALLEN-BRADLEY PANELVIEW  
PLUS 7 10"

### SAFETY SYSTEM

CATEGORY 3

### DISCHARGE ORIENTATION

INLINE

### ENCLOSURE MAIN PANEL

PAINTED (NEMA 4)  
STAINLESS STEEL (NEMA 4X)

### ENCLOSURE PANEL COOLING

VORTEX  
HEAT EXCHANGER  
OR AIR-CONDITIONER

### MACHINE LENGTH

6' 2"  
1880 mm

### MACHINE WIDTH

3' 2"  
965 mm

### MACHINE HEIGHT

7' 6"  
2286 mm

### ADDITIONAL FEATURE

PLATINUM LINE MACHINE  
(MODULAR DESIGN)

### ADDITIONAL FEATURE

TOOL-LESS CHANGEOVER

### STATUS GLOW

BRIGHT INTERNAL LED  
STATUS LIGHTS

### ADDITIONAL FEATURE

MACHINE INTEGRATION



DELKOR  
(800) 328-5558 | (651) 348-6700  
info@delkorsystems.com  
4300 Round Lake Road W. | St Paul, MN