

F SERIES CLOSER



MACHINE FEATURES & SPECS

CHANGEOVER TIME

1

MINUTE

COMPACT FOOTPRINT

6' x 3'

FRAME

SPEED PER MINUTE

60

CASES

PACKAGE FORMATS

5

CASES | TRAYS | HSC
RSC | RRP

UP TO

99%

MAX RELIABILITY

MACHINE HAND

RIGHT HAND
LEFT HAND

SYSTEM PLC

ALLEN-BRADLEY
COMPACT LOGIX

ENCLOSURE MAIN PANEL

PAINTED (NEMA 4)
STAINLESS STEEL (NEMA 4X)

MACHINE HEIGHT

7' 6"
2290 mm

ADDITIONAL FEATURE

PLATINUM LINE MACHINE
(MODULAR DESIGN)

FRAME MATERIALS

PAINTED CARBON STEEL
TUBELESS STAINLESS STEEL
STAINLESS STEEL

SYSTEM HMI

ALLEN-BRADLEY PANELVIEW
PLUS 7 10"

ENCLOSURE PANEL COOLING

VORTEX
HEAT EXCHANGER
AIR-CONDITIONER

STATUS GLOW

BRIGHT INTERNAL LED
STATUS LIGHTS

ADDITIONAL FEATURE

TOOL-LESS
CHANGEOVER

UTILITIES POWER

480 VAC
50 - 60HZ
30 AMPS

SAFETY SYSTEM

CATEGORY 3

MACHINE LENGTH

6' 2"
1880 mm (INTEGRATED)

ADDITIONAL FEATURE

MACHINE INTEGRATION

UTILITIES AIR

15 SCFM @ 80 PSIG

DISCHARGE ORIENTATION

INCLINE

MACHINE WIDTH

3' 2"
965 mm

ADDITIONAL FEATURE

REJECT BIN OPTION
OPEN FLAP REJECT OPTION



DELKOR SYSTEMS
(800) 328-5558 | (651) 348-6700
inform@delkorsystems.com
4300 Round Lake Road W. | Minneapolis, MN

Rev: 07/25