

L SERIES LIDDER



SPECS

PRODUCT UPDATES

PACKAGE TYPES

2

RRP, PAPERBOARD LIDS

COMPACT FOOTPRINT

11'x4'

FRAME

MAX RATE

110

PACKAGES PER MINUTE

MACHINE HAND

RIGHT HAND
LEFT HAND

FRAME MATERIALS

STAINLESS STEEL

UTILITIES POWER

480 VAC
50 - 60HZ
30 AMPS

UTILITIES AIR

15 SCFM @ 80 PSIG

SYSTEM PLC

ALLEN-BRADLEY
COMPACT LOGIX

SYSTEM HMI

ALLEN-BRADLEY PANELVIEW
PLUS 7 10"

SAFETY SYSTEM

CATEGORY 3

DISCHARGE ORIENTATION

RIGHT HAND | LEFT HAND
INLINE (REQUIRES 90 DEGREE
DISCHARGE TRANSFER)

ENCLOSURE MAIN PANEL

PAINTED (NEMA 4)
STAINLESS STEEL (NEMA 4X)

ENCLOSURE PANEL COOLING

VORTEX
HEAT EXCHANGER
OR AIR-CONDITIONER

MACHINE LENGTH

11' 6.5"
3518 mm

MACHINE WIDTH

4' 6"
1372 mm

MACHINE HEIGHT

6' 6"
1981 mm

STATUS GLOW

BRIGHT INTERNAL LED
STATUS LIGHTS

ADDITIONAL FEATURE

TOOL-LESS
CHANGEOVER



DELKOR
(800) 328-5558 | (651) 348-6700
info@delkorsystems.com
4300 Round Lake Road W. | St Paul, MN