PERFORMANCE SERIES CASE PACKER



SPECSPRODUCT UPDATES

CHANGEOVER TIME

8

MINUTES

SPEED PER MINUTE

45

PACKAGES

SPEED PER MINUTE

200

PRODUCTS

PACKAGE TYPES

5

CASES, TRAYS, RRP, ALDI, SPOT-PAK COMPACT FOOTPRING

6'×6'

FRAME

MACHINE HAND

RIGHT HAND LEFT HAND

SYSTEM PLC

ALLEN-BRADLEY COMPACT LOGIX

ENCLOSURE MAIN PANEL

PAINTED (NEMA 4) STAINLESS STEEL (NEMA 4X)

MACHINE HEIGHT

7' 6" 2290 mm (WITH GANTRY DOWN)

ADDITIONAL FEATURE

PLATINUM LINE MACHINE (MODULAR DESIGN)

FRAME MATERIALS

PAINTED CARBON STEEL TUBELESS STAINLESS STEEL OR STAINLESS STEEL

SYSTEM HMI

ALLEN-BRADLEY PANELVIEW PLUS 7 10"

ENCLOSURE PANEL COOLING

VORTEX HEAT EXCHANGER OR AIR-CONDITIONER

STATUS GLOW

BRIGHT INTERNAL LED STATUS LIGHTS

ADDITIONAL FEATURE

TOOL-LESS CHANGEOVER

UTILITIES POWER

480 VAC 50-60HZ 60 AMPS

SAFETY SYSTEM

CATEGORY 3

MACHINE LENGTH

6' 2" 1880 mm

ADDITIONAL FEATURE

REJECT BIN OPTION

ADDITIONAL FEATURE

MISS-PICK AND CRASH DETECTION

UTILITIES AIR

20 SCFM @ 80 PSIG

DISCHARGE ORIENTATION

INLINE COUNTERFLOW

MACHINE WIDTH

6' 2" 1880 mm

ADDITIONAL FEATURE

PATENTED TECHNOLOGY

