

# S SERIES CLOSER



## SPECS

## PRODUCT UPDATES

### CHANGEOVER TIME

2

MINUTES

### INTELLIGENT POSITION

PATENTED

TECHNOLOGY

### SPEED PER MINUTE

200

PACKAGES

### PACKAGE TYPES

2

TRI-SEAL CARTONS,  
FRONT FLAP SEAL

### RAPID DELIVERY

8-12

WEEKS

### MACHINE HAND

RIGHT HAND  
LEFT HAND  
(COVER LEFT OR RIGHT)

### SYSTEM PLC

ALLEN-BRADLEY  
COMPACT LOGIX

### ENCLOSURE MAIN PANEL

PAINTED (NEMA 4)  
STAINLESS STEEL (NEMA 4X)

### MACHINE HEIGHT

6' 10"  
2083 mm

### ADDITIONAL FEATURE

TOOL-LESS  
CHANGEOVER

### FRAME MATERIALS

STAINLESS STEEL

### SYSTEM HMI

ALLEN-BRADLEY PANELVIEW  
PLUS 7 10"

### ENCLOSURE PANEL COOLING

VORTEX  
HEAT EXCHANGER  
OR AIR-CONDITIONER

### STATUS GLOW

BRIGHT INTERNAL LED  
STATUS LIGHTS

### UTILITIES POWER

480 VAC  
50 - 60HZ  
30 AMPS

### SAFETY SYSTEM

CATEGORY 3

### MACHINE LENGTH

10'  
3048 mm

### ADDITIONAL FEATURE

PATENTED TECHNOLOGY  
INTEL POSITIONING

### UTILITIES AIR

15 SCFM @ 80 PSIG

### DISCHARGE ORIENTATION

RIGHT HAND | LEFT HAND  
INLINE (REQUIRES 90 DEGREE  
DISCHARGE TRANSFER)

### MACHINE WIDTH

9' 3"  
2819 mm

### ADDITIONAL FEATURE

REJECT BIN OPTION  
OPEN FLAP REJECT OPTION



DELKOR  
(800) 328-5558 | (651) 348-6700  
info@delkorsystems.com  
4300 Round Lake Road W. | St Paul, MN