

TRAYFECTA G SERIES FORMER



SPECS

PRODUCT UPDATES

CHANGEOVER TIME

3

MINUTES

ROBOT TYPE

GANTRY

CONTROLLED SYSTEM

SPEED PER MINUTE

35

PACKAGES

PACKAGE FORMATS

3

CASES, TRAYS, RRP

MACHINE ORIENTATION

CUSTOM

FLEXIBLE LAYOUT

MACHINE HAND

RIGHT HAND
LEFT HAND

SYSTEM PLC

ALLEN-BRADLEY
COMPACT LOGIX

ENCLOSURE MAIN PANEL

PAINTED (NEMA 4)
STAINLESS STEEL (NEMA 4X)

MACHINE HEIGHT

10' 8"
3251 MM

ADDITIONAL FEATURE

PATENTED TECHNOLOGY

FRAME MATERIALS

PAINTED CARBON STEEL
OR STAINLESS STEEL

SYSTEM HMI

ALLEN-BRADLEY PANELVIEW
PLUS 7 10"

ENCLOSURE PANEL COOLING

VORTEX
HEAT EXCHANGER
OR AIR-CONDITIONER

STATUS GLOW

BRIGHT INTERNAL LED
STATUS LIGHTS

UTILITIES POWER

480 VAC
50-60HZ
60 AMPS

SAFETY SYSTEM

CATEGORY 3

MACHINE LENGTH

15' to 11" to 16' 10"
4851 mm to 5131 mm

ADDITIONAL FEATURE

TOOL-LESS
CHANGEOVER

UTILITIES AIR

25 SCFM @ 80 PSIG

DISCHARGE ORIENTATION

INLINE
RIGHT
LEFT

MACHINE WIDTH

4' 6" to 7' 11"
1372 mm to 2413 mm

ADDITIONAL FEATURE

CRASH DETECTION
275 BLACK CAPACITY
(B FLUTE CASES)



DELKOR

(800) 328-5558 | (651) 348-6700

info@delkorsystems.com

4300 Round Lake Road W. | St Paul, MN