

TRAYFECTA S SERIES FORMER



SPECS

PRODUCT UPDATES

CHANGEOVER TIME

3

MINUTES

FORMING HEADS

1-4

VARIABLE
CONFIGURATION

SPEED PER MINUTE

150

PACKAGES

PACKAGE FORMATS

3

CARTONS, CASES, TRAYS

RAPID DELIVERY

8-12

WEEKS

MACHINE HAND

RIGHT HAND
LEFT HAND

FRAME MATERIALS

STAINLESS STEEL

UTILITIES POWER

480 VAC
50-60HZ
30 AMPS

UTILITIES AIR

5 SCFM @ 80 PSIG

SYSTEM PLC

ALLEN-BRADLEY
COMPACT LOGIX

SYSTEM HMI

ALLEN-BRADLEY PANELVIEW
PLUS 7 10"

SAFETY SYSTEM

CATEGORY 3

DISCHARGE ORIENTATION

INLINE
RIGHT
LEFT

ENCLOSURE MAIN PANEL

PAINTED (NEMA 4)
STAINLESS STEEL (NEMA 4X)

ENCLOSURE PANEL COOLING

VORTEX
HEAT EXCHANGER
OR AIR-CONDITIONER

MACHINE LENGTH

10' 6" to 12' 7"
3200 mm to 3835 mm

MACHINE WIDTH

4' 3" to 7' 11"
1295 mm to 2413 mm

MACHINE HEIGHT

7' 2"
2184 mm

STATUS GLOW

BRIGHT INTERNAL LED
STATUS LIGHTS

ADDITIONAL FEATURE

TOOL-LESS
CHANGEOVER

ADDITIONAL FEATURE

CRASH DETECTION
700 X .020
PAPERBOARD CAPACITY



DELKOR
(800) 328-5558 | (651) 348-6700
info@delkorsystems.com
4300 Round Lake Road W. | St Paul, MN