

V SERIES CASE PACKER



SPECS

PRODUCT UPDATES

CHANGEOVER TIME

5

MINUTES

MAX PACKAGE WEIGHT

2

LBS

SPEED PER MINUTE

600

PRODUCTS
(up to 100 PER ROBOT)

PACKAGE TYPES

2

CASES | TRAYS

ROBOT MODEL

FANUC

M2iA

MACHINE HAND

RIGHT HAND
LEFT HAND

FRAME MATERIALS

PAINTED CARBON STEEL
OR STAINLESS STEEL

UTILITIES POWER

480 VAC
50-60HZ
30 AMPS

UTILITIES AIR

20 SCFM @ 80 PSIG

SYSTEM PLC

ALLEN-BRADLEY
COMPACT LOGIX

SYSTEM HMI

ALLEN-BRADLEY PANELVIEW
PLUS 7 10"

SAFETY SYSTEM

CATEGORY 3

DISCHARGE ORIENTATION

INLINE
COUNTERFLOW

ENCLOSURE MAIN PANEL

PAINTED (NEMA 4)
STAINLESS STEEL (NEMA 4X)

ENCLOSURE PANEL COOLING

VORTEX
HEAT EXCHANGER
OR AIR-CONDITIONER

ENCLOSURE FANUC CABINET

NEMA 1
OPTIONAL: STAINLESS
ENCLOSURE (NEMA 4X)

ENCLOSURE CAMERA

OPTIONAL: STAINLESS
STEEL (NEMA 4) WITH
AIR BLAST

MACHINE LENGTH

4' 2" (EACH CELL)
1270 mm (EACH CELL)

MACHINE WIDTH

7' 2"
2184 mm

MACHINE HEIGHT

11' 8"
3556 mm

STATUS GLOW

BRIGHT INTERNAL LED
STATUS LIGHTS

ADDITIONAL FEATURE

TOOL-LESS
CHANGEOVER

ADDITIONAL FEATURE

REJECT BIN OPTION

ADDITIONAL FEATURE

CRASH DETECTION



DELKOR

(800) 328-5558 | (651) 348-6700

info@delkorsystems.com

4300 Round Lake Road W. | St Paul, MN